

EXISTING DRIVEWAY

- SIDEWALK

EXISTING DRIVEWAY

DRIVEWAY GEOMETRICS

N. T.S.

ST.1.4

CORNER RADIUS

25' MINIMUM

MIN.

- 2. ALL DRIVEWAY LOCATIONS SHALL BE SUBJECT TO REVIEW AND APPROVAL BY THE CITY.
- 3. GRADE CHANGES BEHIND RIGHT-OF-WAY TO BE ROUNDED OFF WITH A 2' RADIUS BEGINNING AT RIGHT-OF-WAY LINE.
- 4. CONTRACTION JOINT SPACING IN DRIVEWAY SHALL BE AT 12' MAX. (BOTH DIRECTIONS)
- 5. DETAIL ST.1.1 SHALL ONLY BE USED WHEN RIGHT-OF-WAY CONDITIONS PROHIBIT THE USE OF DETAILS ST.1.2 OR ST.1.3.
- 6. CLASS III DRIVEWAY DESIGN REQUIRES APPROVAL BY ENGINEER PRIOR TO INSTALLATION.
- 7. ANY EXISTING CURB & GUTTER SHALL BE COMPLETELY REMOVED TO THE TOE OF THE GUTTER LINE FOR INSTALLATION OF DRIVEWAY. EXISTING A.C. PAVEMENT SHALL BE SAWCUT TO A NEAT LINE WITH A.C. PATCH, MATCHING EXISTING PAVEMENT THICKNESS, PLACED ON TOP OF P.C. BASE.
- 8. CURB RADII THAT ARE INTEGRAL WITH DRIVEWAYS (DETAIL ST.1.3) ARE CONSIDERED INCIDENTAL TO DRIVEWAYS. CURB AND GUTTER ACROSS TOE OF DRIVEWAYS WILL BE MEASURED AND PAID FOR SEPARATELY AS CURB AND GUTTER.

Fort

REE

ST

DRIVEWAYS

IMPROVEMENT

Drawings

Standard

Construction

Public

CITY OF FORT SMITH
Engineering Department
623 Garrison Avenue, Room 409
Fort Smith, Arkansas 72901
ne (479)784-2225 Fax (479)784-2245

Project: Details
Date: NOV 2012
Scale: As Shown
Drawn By: RBR
Dwg. No.: ST1
Sheet No: 15